

Orbital sanders

**NEW
OIL FREE!**

Velcro Palm Orbital Sanders

These Red Rooster palm sanders are vibration-reduced. The body has a rubber cover with a soft touch for maximum grip.

Applications in: car-bodywork, metal- and woodworking industry. No additional lubrication of the air is required.

Specifications:

- Ergonomic design, well balanced
- Exhaust air is silenced
- Velcro pad
- Lightweight
- Adjustable speed.



RRI-5125-2CV


 RRI-5125-2NV / RRI-6150-2NV
 RRI-5125-5NV / RRI-6150-5NV

 RRI-5125-2CV / RRI-6150-2CV
 RRI-5125-5CV / RRI-6150-5CV

 RRI-5125-2SV / RRI-6150-2SV
 RRI-5125-5SV / RRI-6150-5SV

Type	Brand	Pad size mm	Hub mm	RPM	Power kW	Spindle	Air cons. l/s	Weight kg	Inlet-thread	Hose diameter mm	Vibration m/s ²	Noise Level dB(A)
RRI-5125-2NV ¹⁾	RRI	125	2,5	12.000	0,3	5/16" UNF	4,9	0,76	PT 1/4"	10	<2,5	76
RRI-5125-2CV ¹⁾	RRI	125	2,5	12.000	0,3	5/16" UNF	4,9	0,76	PT 1/4"	10	<2,5	76
RRI-5125-2SV ¹⁾	RRI	125	2,5	12.000	0,3	5/16" UNF	4,9	0,78	PT 1/4"	10	<2,5	84
RRI-5125-5NV ¹⁾	RRI	125	5	12.000	0,3	5/16" UNF	4,9	0,76	PT 1/4"	10	<2,5	76
RRI-5125-5CV ¹⁾	RRI	125	5	12.000	0,3	5/16" UNF	4,9	0,78	PT 1/4"	10	<2,5	76
RRI-5125-5SV ¹⁾	RRI	125	5	12.000	0,3	5/16" UNF	4,9	0,78	PT 1/4"	10	<2,5	84
RRI-6150-2NV ¹⁾	RRI	150	2,5	12.000	0,3	5/16" UNF	4,9	0,76	PT 1/4"	10	<2,5	76
RRI-6150-2CV ¹⁾	RRI	150	2,5	12.000	0,3	5/16" UNF	4,9	0,78	PT 1/4"	10	<2,5	76
RRI-6150-2SV ¹⁾	RRI	150	2,5	12.000	0,3	5/16" UNF	4,9	0,78	PT 1/4"	10	<2,5	84
RRI-6150-5NV ¹⁾	RRI	150	5	12.000	0,3	5/16" UNF	4,9	0,76	PT 1/4"	10	<2,5	84
RRI-6150-5CV ¹⁾	RRI	150	5	12.000	0,3	5/16" UNF	4,9	0,78	PT 1/4"	10	<2,5	76
RRI-6150-5SV ¹⁾	RRI	150	5	12.000	0,3	5/16" UNF	4,9	0,78	PT 1/4"	10	<2,5	84

¹⁾ Standard delivered with Velcro disk. NV = No dust extraction / CV = For connection to central dust extraction / SV = Self created Vacuum for dust extraction