

# Shut-off Impulse wrench

## YLT-Series

HIGH PERFORMANCE



## YLT Series

- **Maximum accuracy**  
Extreme accurate and fast. Repeatability, new principle: shut-off valve and reset
- **Maximum durability**  
Check valve mechanism reduces load on the O-ring inside the oil pulse mechanism.
- **Maximum ergonomics**  
Ergo touch / Ergo grip / Ergo trigger
- **Maximum environment**  
Reduction of CO2 emission / Low noise / Low vibration

## Yokota Impulse Wrenches

- Have proven themselves worldwide in the leading car- and general assembly industry, tightening threaded fasteners.
- Are light, powerful and small and very importantly they have no kick-back.
- Are extremely low weight and good for use with non-lubricated air.

Type	Square/ hex drive	Bolt capacity mm	RPM	Torque Nm*	Air- cons l/s	Inlet- thread	Weight kg	Hose diameter mm	Length A mm	Spindle offset B mm	Vibration m/s <sup>2</sup>	Noise level dB(A)
YLT60A	1/4" Hex	6	5.300	6,0 - 13,0	5,5	PT 1/4"	0,95	6	164	22,5	1,4	72
YLT70A	1/4" Hex	6-8	6.800	13,0 - 28,0	6,0	PT 1/4"	1,01	6	177	23	1,8	74
YLT60E	3/8" Square	6	5.300	7,0 - 15,5	5,5	PT 1/4"	0,95	6	164	22,5	1,4	72
YLT70E	3/8" Square	6-8	6.800	15,0 - 32,0	6,0	PT 1/4"	1,01	6	177	23	1,8	74
YLT80E	3/8" Square	8	6.800	30,0 - 55,0	7,3	PT 1/4"	1,12	6	187	24,5	1,9	78
YLT110E	1/2" Square	10-12	5.800	50 - 85	8,3	PT 1/4"	1,51	9,5	194	28,5	1,8	81
YLT120E	1/2" Square	12	5.400	70 - 115	8,6	PT 1/4"	1,79	9,5	201	31	2,2	83
YLT140E	1/2" Square	14	5.200	110 - 150	11,8	PT 1/4"	2,08	9,5	214	32,5	5,2	85

\* The specified torques are to be used as a guidance only.